



**Aluminum/Aluminum
m
Blind Rivet
Dome Head**

Length Unit: mm

d	L	Grip Range		Hole Size Φ	dk	k max	dm max	p min	Minimum Compressive N	Minimum Shear Force N
		min	max							
Φ3.2 +0.08 -0.15	6.0	1.0	3.5	3.3-3.4	5.8-6.7	1.3	2.0	27	400	350
	8.0	3.5	5.0							
	10.0	5.0	7.0							
	12.0	7.0	9.0							
	14.0	9.0	11.0							
	16.0	9.0	12.5							
	18.0	12.0	14.5							
	20.0	13.0	16.5							
25.0	15.0	21.0								
Φ4.0 +0.08 -0.15	6.0	1.0	3.0	4.1-4.2	6.9-8.4	1.7	2.5	27	900	700
	8.0	3.0	5.0							
	10.0	4.0	6.5							
	12.0	6.0	8.5							
	14.0	7.0	10.5							
	16.0	8.0	12.5							
	18.0	10.0	14.5							
	20.0	12.0	16.0							
	25.0	16.0	21.0							
	30.0	21.0	26.0							
	35.0	26.0	30.5							
40.0	30.5	35.0								
Φ4.8 +0.08 -0.15	6.0	1.0	2.5	4.9-5.0	8.3-10.1	2.0	3.0	27	1300	850
	8.0	2.5	4.0							
	10.0	4.0	6.0							
	12.0	6.0	8.0							
	14.0	8.0	10.0							
	16.0	8.0	12.0							
	18.0	10.0	14.0							
	20.0	12.0	16.0							
	25.0	16.0	21.0							
	30.0	21.0	25.0							
	35.0	25.0	30.0							
40.0	30.0	35.0								
50.0	40.0	45.0								